



7050 Ceramic SMD Crystals

■ Holder Type: CG(2 pads 7.0×5.0)

Frequency Range:

6.00MHz to 125.00MHz

Features:

- High Reliability & Low Cost Unit
- Tight Stability & Extended Temperature Available
- Lead-free Type
- For automotive applications, please contact our sales representative



Actual Size



QUARTZ
CRYSTALS

■ Standard Specifications

Item	Value
Frequency Range	6.00 to 125.00MHz
Frequency Tolerance	±30ppm (tighter tolerance also available)
Frequency Tolerance over Temperature range	±50ppm (tighter tolerance also available)
Operating Temperature Range	-10 °C to +60 °C (other operating range also available)
Operable Temperature Range	-40 °C to +85 °C
Equivalent Series Resistance (ESR)	Please refer to the ESR Table
Drive Level	50µW Typ. (300µW Max.)
Load Capacitance	8pF (3pF, 4.5pF, 6pF and series also available)
Ageing	±5ppm/year

■ ESR Table

Frequency Range (MHz)	Mode	Standard ESR (Ohm)
6 to 8	AT Cut Fund.	150
8 to 9	AT Cut Fund.	100
9 to 10	AT Cut Fund.	60
10 to 11	AT Cut Fund.	50
11 to 13	AT Cut Fund.	40
13 to 50	AT Cut Fund.	30
26 to 125	3rd Overtone	100

Note:

1. Manufacturer reserves the right to change the specification and content of this product for improvement without notification.
2. Custom specification is welcome. Please contact our sales representative for further details.
3. If the crystal is intended for applications which have direct impact on human life and properties, and require a high degree of reliability and safety concerns, customers must provide full information such as but not limit to the application, electrical and reliability specification at the inquiry beginning stage.
4. Customers have to agree to the "Guideline for handling crystal units" and "Standard Terms and Condition of Sales" which is printed this catalog before placing orders to our company or our distributors. There are also unpredictable factors such as applied condition, oscillation margin and etc and customers must check them beforehand. In case of queries, please do not fail to send inquiry to our company before ordering.

http://www.hongkongcrystal.com
 E-mail: China: sales.cn@hongkongcrystal.com
 HongKong/Overseas: inquiry@hongkongcrystal.com


HongKong/Overseas
 Shenzhen: T:+86

TELCONA

TELCONA AG • Im Vorderasp 4 • CH-8154 Oberglatt • Switzerland
 Tel. +41 (0) 44 860 25 50 • Fax +41 (0) 44 860 28 22
 info@telcona.com • www.telcona.com




■ Dimensions (mm) and Solder Pad Layout (mm)



QUARTZ
CRYSTALS

■ Tape & Reel (mm)



	8x4.5 SMD	7x5 SMD	6x3.5 SMD	5x3.2 SMD	4x2.5 SMD	3.2x2.5 SMD	2.5x2.0 SMD
T A P E	PART NO.	48065002	48065001	48060036	48065023	48065018	48065014
	W	16.00 ^{+0.3} _{-0.1}	16.00 ^{+0.3} _{-0.1}	16.00 ^{+0.3} _{-0.1}	12.00 ^{+0.3} _{-0.1}	12.00 ^{+0.30} _{-0.1}	8.00 ^{+0.30} _{-0.1}
	A0	8.00±0.1	8.00±0.1	8.00±0.1	8.00±0.1	8.00±0.10	4.00±0.10
	P	4.80±0.1	5.40±0.1	3.75±0.1	3.50±0.1	2.70±0.10	2.80±0.10
	BQ	8.30±0.1	7.40±0.1	6.20±0.1	5.40±0.1	4.20±0.10	3.60±0.10
	K0	1.70±0.1	1.65±0.1	1.20±0.1	1.50±0.1	1.00±0.10	1.25±0.10
	P0	4.00±0.1	4.00±0.1	4.00±0.1	4.00±0.1	4.00±0.10	4.00±0.10
	F	7.50±0.1	7.50±0.1	7.50±0.1	5.50±0.1	5.50±0.10	3.50±0.10
	D1	1.50 ^{+0.10} _{-0.05}	1.50 ^{+0.10} _{-0.05}	1.50 ^{+0.10} _{-0.05}	1.50 ^{+0.10} _{-0.05}	1.50 ^{+0.10} _{-0.05}	1.00 ^{+0.10} _{-0.05}
	T1	0.30±0.05	0.30±0.05	0.30±0.05	0.30±0.05	0.30±0.05	0.20±0.05
R E E L	PART NO.	48060024	48060050		48065020	48065026	48065026
	C	Ø178.0±1	Ø330±1		Ø178±1	Ø330±1	Ø330±1
	D	Ø50.0±0.5	Ø100.0±1		Ø60.0±0.5	Ø100.0±1	Ø100.0±1
	H	16.5±0.5	16.5±0.5		13.1±0.2	12.5±0.5	13.1±0.2
	T	1.50±0.2	2.3±0.3		1.2±0.2	2.3±0.3	1.2±0.2
STANDARD PACKING QTY/REEL		1000PCS	4000PCS		1000PCS	5000PCS	2000PCS
MAXIMUM PACKING QTY/REEL		1300PCS	1300PCS	1800PCS	4600PCS	4800PCS	6300PCS
					1400PCS	5500PCS	2100PCS
						7600PCS	3500PCS
							3800PCS